

AC

Case: Alicherry 8-8-7-23
Serial No. 10/728178
Filing Date: December 4, 2003



(11) **EP 1 263 255 A2**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication: 04.12.2002 Bulletin 2002/49 (51) Int Cl.7: **H04Q 7/38**

(21) Application number: **02100581.4**

(22) Date of filing: **30.05.2002**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **GILKES, Alan M.**
Plano, TX 75075 (US)
• **PANASIK, Carl**
Garland, TX 75044 (US)

(30) Priority: **01.06.2001 US 872598**


(74) Representative: **Holt, Michael et al**
Texas Instruments Ltd.,
EPD MS/13,
800 Pavilion Drive
Northampton Business Park,
Northampton NN4 7YL (GB)

(71) Applicant: **Texas Instruments Incorporated**
Dallas, Texas 75251 (US)

(54) **Location estimation in narrow bandwidth wireless communication systems**

(57) The phase difference between a known stable reference signal (11) and a known signal output by a wireless mobile communication device (5, 5B) is determined at several known locations (1-4, 1B-4B). The location of the wireless mobile communication device is then determined from the phase difference information.

Also, the approximate location of a wireless mobile communication device (5A) can be estimated by transmitting a message from the device at a predetermined power level (71), and determining where among a plurality of predetermined locations (1A-4A) the transmitted message has been received.



EP 1 263 255 A2

Description

FIELD OF THE INVENTION

[0001] The invention relates generally to location determination in wireless communications and, more particularly, in narrow bandwidth wireless communication systems.

BACKGROUND OF THE INVENTION

[0002] Present telecommunication system technology includes a wide variety of wireless networking systems associated with both voice and data communications. An overview of several of these wireless networking systems is presented by Amitava Dutta-Roy, *Communications Networks for Homes*, IEEE Spectrum, pg. 26, Dec. 1999. Therein, Dutta-Roy discusses several communication protocols in the 2.4 GHz band, including IEEE 802.11 direct-sequence spread spectrum (DSSS) and frequency-hopping (FHSS) protocols. A disadvantage of these protocols is the high overhead associated with their implementation. A less complex wireless protocol known as Shared Wireless Access Protocol (SWAP) also operates in the 2.4 GHz band. This protocol has been developed by the HomeRF Working Group and is supported by North American communications companies. The SWAP protocol uses frequency-hopping spread spectrum technology to produce a data rate of 1 Mb/sec. Another less complex protocol is named Bluetooth after a 10th century Scandinavian king who united several Danish kingdoms. This protocol also operates in the license-free 2.4 GHz band and advantageously offers short-range wireless communication between Bluetooth devices without the need for a central network.

[0003] The Bluetooth system provides a 1 Mb/sec data rate with low energy consumption for battery powered devices operating in the 2.4-GHz ISM (industrial, scientific, medical) band. The current Bluetooth system provides a 10-meter range and a maximum asymmetric data transfer rate of 723 kb/sec. The system supports a maximum of three voice channels for synchronous, CVSD-encoded transmission at 64 kb/sec. The Bluetooth system treats all radios as peer units except for a unique 48-bit address. At the start of any connection, the initiating unit is a temporary master. This temporary assignment, however, may change after initial communications are established. Each master may have active connections of up to seven slaves. Such a connection between a master and one or more slaves forms a "piconet." Link management allows communication between piconets, thereby forming "scatternets." Any Bluetooth device can assume the role of master or slave. For example, typical Bluetooth master devices include cordless phone base stations, local area network (LAN) access points, laptop computers, or bridges to other networks. Bluetooth slave devices may include

cordless handsets, cell phones, headsets, personal digital assistants, digital cameras, or computer peripherals such as printers, scanners, fax machines and other devices.

[0004] The Bluetooth protocol uses time-division duplex (TDD) to support bi-directional communication. Frequency hopping permits operation in noisy environments and permits multiple piconets to exist in close proximity. The frequency hopping scheme permits up to 1600 hops per second over 79 1-MHz channels or the entire 2.4-GHz ISM spectrum. Various error correcting schemes permit data packet protection by 1/3 and 2/3 rate forward error correction. Further, Bluetooth uses retransmission of packets for guaranteed reliability. These schemes help correct data errors, but at the expense of throughput.

[0005] The Bluetooth protocol is specified in detail in Specification of the Bluetooth System, Version 1.0A, July 26, 1999, which is incorporated herein by reference.

[0006] Techniques have been developed for identifying the geographic location of a wireless communication device, for example, in emergency situations or to provide travel directions. However, these techniques can be particularly difficult to implement when the devices are operating indoors. Global Positioning System (GPS) satellite reception may be impossible, and wireless telephony may be difficult at best in many locations, such as the inside of factories, high-rise buildings, parking garages, shopping malls, subway/train stations and airport terminals.

[0007] It is therefore desirable to provide the capability of identifying the geographic location of a wireless mobile communication device that is operating indoors.

[0008] Many conventional approaches to precision location identification make use of so-called "time of arrival" techniques. One difficulty with time of arrival techniques is the uncertainty of time, which can occur at several locations. For example, if it is desired to locate a particular wireless mobile communication device, and that device broadcasts a beacon in several time slots, with each time slot dedicated to a respective base station, then the uncertainty of the wireless mobile communication device's clock can be a source of error in the location identification operation. If the base stations are operated with respectively independent clocks, then the uncertainty associated with the independent clocks can also be a source of error in the location identification operation.

[0009] It is therefore desirable to provide location identification techniques that avoid disadvantageous time uncertainties.

[0010] Some conventional techniques utilize a wide frequency signal for location identification. Such a wide bandwidth signal permits a very narrow pulse width, the timing of which can be precisely measured. However, this wide bandwidth signal is not available in narrow bandwidth wireless communication systems such as Bluetooth systems. For example, the communication

bandwidth in Bluetooth systems is only 1 MHz. Therefore, the smallest bit length is 1 microsecond. Disadvantageously, an error of 1 microsecond in timing corresponds to a distance uncertainty of 300 meters (3×10^8 meters/second $\times 10^{-6}$ seconds). Another problem encountered in systems such as Bluetooth is that the preamble defined by the Bluetooth protocol is only long enough to insure that all data bits are sampled without error. There is no determination of the start of a bit, or definition of the bit edge.

[0011] It is therefore desirable to improve the precision of location identification in narrow bandwidth wireless communication systems.

[0012] It is also desirable in view of the foregoing to provide location identification techniques that do not require the capability of determining a start bit or defining a bit edge.

[0013] The present invention determines, at several known locations, the phase difference between a known stable reference signal and a known signal output by the wireless mobile communication device that is being located. The location of the wireless communication device can be determined from the phase difference information obtained at the predetermined locations. This advantageously permits precise location estimation indoors, using a relatively narrow bandwidth signal, and also advantageously avoids the aforementioned problems of time uncertainties and bit definition. Further according to the invention, the approximate location of a wireless mobile communication device can be estimated by transmitting a message from the device at a predetermined power level, and determining where among a plurality of predetermined locations the transmitted message has been received.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014]

FIGURE 1 diagrammatically illustrates pertinent portions of an exemplary embodiment of a wireless communication system including location determination according to the invention.

FIGURE 2 diagrammatically illustrates pertinent portions of exemplary embodiments of a location marker according to the invention.

FIGURE 2A illustrates a portion of FIGURE 2 in greater detail.

FIGURE 3 diagrammatically illustrates further capabilities of the embodiment of FIGURE 1.

FIGURE 4 diagrammatically illustrates pertinent portions of an embodiment similar to FIGURE 1 but wherein the location solution processor is provided in a mobile device which can initiate location esti-

mation with respect to another mobile device.

FIGURE 5 illustrates exemplary operations which can be performed by the embodiments of FIGURES 1-4.

FIGURE 6 diagrammatically illustrates pertinent portions of an exemplary embodiment of a wireless communications system according to the invention that can roughly approximate the location of a mobile communication device.

FIGURE 7 illustrates exemplary operations which can be performed by the embodiment of FIGURE 6.

DETAILED DESCRIPTION

[0015] The present invention recognizes two possible approaches to precision location estimation in narrow bandwidth systems. A first approach is the use of spread spectrum waveforms. A spread spectrum waveform can be sent, for example in a conventional Bluetooth data packet. A Barker code could be used for such a spread spectrum application, because all of its compressed-pulse time sidelobes are of uniform size, and the peak value is the bit-length (or processing gain). The use of a compressed pulse would permit precision location (by a factor of the processing gain) using a comparator to find the exact sample time. Although the longest Barker code is 13 bits, Barker codes can be concatenated by multiplying each successive Barker code by another. For example, a length 3 Barker code can be multiplied (convolved) with a length 13 Barker code to generate a unique code of 36 bits.

[0016] To determine the exact bit transition in the spread spectrum waveform, the waveform must be oversampled by several factors of the bit rate. In fact, each bit transmitted by the mobile device that is being located would need to be oversampled, and the time position of the bits would need to be determined within nanoseconds. It can therefore be seen that the use of spread spectrum waveforms can be expected to require an undesirably large amount of signal processing.

[0017] Another approach according to the present invention is to match the phase of a narrowband signal (transmitted by the mobile device to be located) with a network timing reference. For example, a 1 MHz signal will have a 1 microsecond periodicity. As long as the geographical distances within the location estimation environment are less than 300 meters, the phase of the 1 MHz signal can be detected (relative to a common reference signal) at each of a plurality of known locations, and the distances to the respective locations can then be calculated from the relative phases detected at those locations. Each of the detected phases will be different from the others, and this will provide the needed positioning information.

[0018] FIGURE 1 diagrammatically illustrates parti-

nent portions of an exemplary embodiment of a wireless communication system which can implement location estimation techniques according to the invention. The embodiment of FIGURE 1 includes a wireless mobile communication device 5 whose location is to be determined by the system of FIGURE 1. In the example of FIGURE 1, the mobile communication device 5 is a Bluetooth device, for example a personal digital assistant (PDA), a palmtop computer, an ultralight laptop computer, or a wireless telephone, operating in a Bluetooth system. The device 5 includes a Bluetooth transceiver for use in a variety of short distance wireless information exchanges. One such information exchange is a "Locate Me" message which is transmitted via a Bluetooth wireless communication link at 15 to a plurality of location markers 1-4 which can be conventionally configured to receive Bluetooth wireless communications. As shown in FIGURE 1, the locations markers 1-4 are located at different geographic locations. For example, location marker 1 is located at Cartesian coordinates x_1 , y_1 , z_1 and location marker 2 is located at Cartesian coordinates x_2 , y_2 , z_2 , location marker 3 is located at Cartesian coordinates x_3 , y_3 , z_3 , and location marker 4 is located at Cartesian coordinates x_4 , y_4 , z_4 . The "Locate Me" message transmitted by the mobile device 5 arrives at the various location markers 1-4 at respective arrival times, namely t_1 for location marker 1, t_2 for location marker 2, t_3 for location marker 3 and t_4 for location marker 4.

[0019] According to the invention, the "Locate Me" Bluetooth message includes, for example, a 1 MHz signal embedded therein, and the location markers 1-4 measure the phase difference between this embedded signal and a 1 MHz sine wave frequency reference signal 11 that is produced at a fixed location by a stationary reference oscillator 6 and is distributed to the location markers 1-4. The reference signal 11 can be distributed, for example, by coaxial cable, modified Ethernet or latency-free wireless means. The reference oscillator 6 can be a GPS reference receiver, or any suitable stable reference source, for example, an oven-stabilized quartz oscillator or a Cesium or Rubidium atomic standard oscillator. One reference oscillator 6 may be used to distribute the reference signal 11 over an entire building or campus. In some embodiments, the reference signal 11 has a stability at least four times that of the internal clock of the mobile device 5.

[0020] The 1 MHz signal embedded in the "Locate Me" message can be set, for example, to 1010101010. For the set of location markers 1-4 that receive the same "Locate Me" message from the mobile device 5, the phase difference determined at each location marker is indicative of the time of arrival of the "Locate Me" message at that location marker, relative to the time of arrival of the "Locate Me" message at the other location markers.

[0021] Each of the location markers 1-4 provides to a location solution processor 7 information indicative of

the relative time of arrival of the "Locate Me" message at that particular location marker. This relative time of arrival information is designated in FIGURE 1 as t_{1RA} for location marker 1, t_{2RA} for location marker 2, t_{3RA} for location marker 3 and t_{4RA} for location marker 4. The location solution processor 7 uses this relative time of arrival information, together with other information indicated in FIGURE 1 and discussed in more detail below, to estimate the location of the mobile device 5. The estimated location is designated as x_M , y_M , z_M in FIGURE 1. This estimated location information can then be provided, for example, to emergency service personnel, a location monitoring application, etc.

[0022] Also as shown in FIGURE 1, the "Locate Me" message transmitted by the mobile device 5 includes a unique identifier which is uniquely associated with the mobile device, designated as "unique_ID" in FIGURE 1, and also includes a sequence number that the mobile device 5 assigns to each individual "Locate Me" message, which sequence number is designated in FIGURE 1 as "sequence_number_N". Thus, if the mobile device 5 transmits a sequence of individual "Locate Me" messages, the eighth message in the sequence would have a sequence number of, for example, 8. In addition to the aforementioned relative time of arrival information, the location markers 1-4 provide to the location solution processor 7 the unique identifier and the sequence number associated with the "Locate Me" message from which the relative time of arrival information has been determined. The location markers 1-4 also provide their respective Cartesian coordinates to the location solution processor 7 along with the relative time of arrival information. In other embodiments, the location markers can simply identify themselves to the location solution processor, and the corresponding Cartesian coordinates of the respective location markers can be retrieved by the location solution processor from its own internal storage.

[0023] The combination of the unique identifier, unique_ID, and the sequence number, sequence_number_N, provides a unique "tag" associated with the relative time of arrival information and the Cartesian coordinates provided by a given location marker. The relative time of arrival information and Cartesian coordinates supplied by the different location markers must all have the same "tag" in order to be used by the location solution processor 7 to calculate the location of the mobile device 5 (or any other mobile device).

[0024] FIGURE 2 diagrammatically illustrates pertinent portions of exemplary embodiments of the location markers of FIGURE 1. The location marker illustrated in FIGURE 2 includes a non-volatile storage section designated generally at 25. The Cartesian coordinates x_K , y_K , z_K of the location marker can be stored in the storage section 25 when the location marker is initially positioned, for example affixed to a ceiling or wall of a building or other structure. Site surveys and interior plans

used to construct the surrounding structure can be used to provide the Cartesian coordinates precisely. The Cartesian coordinate system may be defined relative to a local origin that is particularly useful for identifying relative locations within the structure. As another example, the coordinate system could be the Earth-Centered Earth-Fixed (ECEF) coordinate system conventionally used in GPS position calculations. This may be useful for identifying locations within the structure relative to locations at some distance outside of the structure.

[0025] Also at the time that the location marker is installed, a system calibration procedure can be used to measure the propagation delay from the source of the stable frequency reference 11 (see 6 in FIGURE 1) to the location marker. The resulting phase delay parameter ϕ_K is then also stored in the storage section 25. For a set of location markers covering a given area, such as illustrated in FIGURE 1, the differences between the phase delay parameter values must be accounted for in the location solution processing (see 7 in FIGURE 1), but the phase delay parameter values themselves are not required. Thus, for example, in the exemplary illustrated system using a 1 MHz frequency reference, the phase delay parameters ϕ_K of the respective markers can be expressed in radians, and a phase delay value of 0.0 radians can be assigned to the location marker having the shortest propagation delay from the frequency reference source 6 of FIGURE 1.

[0026] The exemplary location marker of FIGURE 2 includes a Bluetooth wireless transceiver having a radio and baseband section 21 and a message processing section 22. The Bluetooth wireless transceiver permits the location marker to exchange Bluetooth wireless communications with other Bluetooth transceivers. For example, the location marker can receive the "Locate Me" message of FIGURE 1 via the antenna 29 of the Bluetooth wireless transceiver. Also, the location marker can use the Bluetooth wireless transceiver to transmit to the location solution processor 7 of FIGURE 1 the aforementioned relative time of arrival information, Cartesian coordinates and associated tag, as shown at 202. In other embodiments, this information can be transmitted to the location solution processor 7 via a wired connection, as illustrated generally at 201 in FIGURE 2.

[0027] The exemplary location marker of FIGURE 2 also includes a 1 MHz phase comparator 23 which can measure the phase difference between the stable 1 MHz reference signal 11, and the 1 MHz waveform embedded in the "Locate Me" message. This latter waveform is extracted from the "Locate Me" message by the radio and baseband section 21, and is forwarded to the phase comparator 23. In the example of FIGURE 2, the phase comparator 23 has a 0.001 cycle (6.2832 milliradian) phase difference resolution capability, which corresponds to an 11.8 inch resolution in the distance between the location marker and the mobile device 5 of FIGURE 1. To compensate for phase jitter in the "Locate Me" message, the phase comparator 23 measures the

phase difference 206 for several successive 1 MHz cycles (e.g., 1000 or more cycles of the embedded waveform), and these successive measurements are averaged by a phase difference averager 24 to produce a phase difference average 205 for the entire "Locate Me" message.

[0028] The averager 24 outputs the average phase difference 205 to a relative arrival time generator 26 which also receives the location marker's phase delay parameter ϕ_K from the storage section 25, and generates therefrom the relative time of arrival, t_{RA} of the "Locate Me" message. The relative time of arrival generator 26 adds the average phase difference 205 to the phase delay parameter ϕ_K , thereby adjusting the average phase difference for the relative phase delay associated with distribution of the reference signal 11 from the source 6 of FIGURE 1 to the location marker. The result is divided by 2B to provide the relative message arrival time t_{RA} in units of microseconds. The above-described average phase difference adjustment and division operations are respectively performed by the phase difference adjuster and divider of FIGURE 2A. The relative message arrival time t_{RA} is then provided to a location solution data output 27 along with the Cartesian coordinates of the location marker (from the storage section 25) and the aforementioned "tag" information (sequence number of the "Locate Me" message and unique identifier of the mobile device 5). The location solution data output combines the relative message arrival time information, the Cartesian coordinates, and the tag information in a message that is transmitted to the location solution processor 7 via either the wired connection 201 (e.g., ethernet) or the wireless connection 202 (e.g., a Bluetooth radio link).

[0029] The above-described operations of the location marker of FIGURE 2 are initiated when the Bluetooth transceiver detects the start of an arriving message. At this time, the radio and baseband section 21 activates the phase comparator 23 and the phase difference averager 24. When the Bluetooth transceiver has received the complete message and has identified it as a "Locate Me" message, the message processing section 22 applies a start signal 204 to both the relative arrival time generator 26 and the location solution data output 27. Also after the complete message has been received and identified as a "Locate Me" message, the message processing section 22 provides the aforementioned tag information to the location solution data output 27.

[0030] Referring again to the location solution processor 7 of FIGURE 1, this processor can be, for example, dedicated to a particular network of location markers for the purpose of calculating precise locations using information received from those location markers. In one exemplary embodiment, the location solution processor 7 uses information from at least 4 non-coplanar location markers and solves simultaneous equations derived from the Cartesian coordinates of the location

markers and the differences between the relative times of arrival t_{RA} reported by the location markers.

[0031] Exemplary FIGURE 3 is generally similar to FIGURE 1, but illustrates that, even when information is available from only three location markers, namely location markers 1, 2 and 4, the location solution processor 7 can still determine the relative proximity of the mobile device 5 to those location markers. In the example of FIGURE 3, the location solution processor uses the information reported by the location markers 1, 2 and 4 to determine that the mobile device 5 is 31 meters closer to location marker 2 than to location marker 4, and is 7 meters closer to location marker 1 than to location marker 2. This relative proximity information is output from the location solution processor 7 at 35, and can be used, for example, by Bluetooth network control for routing messages and balancing message traffic in a Bluetooth network.

[0032] Exemplary FIGURE 4 is also generally similar to FIGURE 1, except another wireless mobile communication device 51 (a Bluetooth device in the example of FIGURE 4) initiates the process of estimating the location of a mobile communication device 5B. The process is initiated when the mobile device 51 broadcasts at 52 a digitally signed "Where Is" message that includes the unique identifier of the mobile device 5B. The message at 52 can be relayed through the Bluetooth network to device 5B, for example via the transceivers of one or more of the location markers 1B-4B, as shown at 42 and 44. This "Where Is" message relaying is also illustrated in FIGURE 2, where the "Where Is" message can be recognized by the message processing section 22 and relayed accordingly.

[0033] When the mobile device 5B receives the relayed message and recognizes that the message includes its unique identifier, the mobile device 5B first examines the digital signature to determine whether the originator of the "Where Is" message (mobile device 51) is authorized to know the location of mobile device 5B. If the mobile device 51 is authorized to know the location of the mobile device 5B, then the mobile device 5B begins transmitting the aforementioned "Locate Me" messages, and the location estimation can thereafter proceed generally as described above with respect to FIGURE 1. Note that the location markers 1B-4B make their respective reports to the mobile device 51 (which is identified by the digital signature in the "Where Is" message) via the Bluetooth network as illustrated generally at 53. The mobile device 51 can include the functionality of the location solution processor 7 of FIGURE 1 in order to calculate the precise location of the mobile device 5B. The above-described operation of the FIGURE 4 embodiment can be useful, for example, when a parent in possession of mobile device 51 wants to determine the location of a lost child who possesses the mobile device 5B.

[0034] FIGURE 5 illustrates exemplary operations which can be performed by the embodiments of FIG-

URES 1-4. After transmission of the "Locate Me" message at 55, a single timing reference (e.g., a stable 1 MHz sine wave) is used at 56 to determine the times of arrival of the "Locate Me" message at a plurality of known locations. Thereafter at 57, the differences between the respective times of arrival are used to estimate the location of the mobile device that transmitted the "Locate Me" message.

[0035] FIGURE 6 diagrammatically illustrates pertinent portions of a further exemplary embodiment of a wireless communication system according to the invention. In the embodiment of FIGURE 6, a Bluetooth-equipped wireless mobile communication device 5A broadcasts an "Approximate Location?" message over a Bluetooth wireless communication link at 62. Each of the location markers 1A-4A that receives the "Approximate Location?" interrogatory responds by transmitting its Cartesian coordinates to the mobile device 5A. As one example, if the mobile device 5A transmits the "Approximate Location?" message at a predetermined, relatively low power level, and receives one or more responses from the location markers 1A-4A, then the location of the mobile device 5A lies within a predetermined distance (e.g., approximately 10 meters) of the Cartesian coordinates specified in the location marker response(s). As another example, if the mobile device 5A transmits the "Approximate Location?" message at a predetermined, relatively high power and receives one or more responses, then the mobile device 5A is known to be located within another predetermined distance (e.g., approximately 100 meters) of the Cartesian coordinates specified in the location marker response(s). The device 5A includes a location estimator which receives the response(s) and can estimate the device's location based on the response(s) and the corresponding Cartesian coordinates.

[0036] For example, in FIGURE 6, if only the location marker 1A responds to the low-power message, then the mobile device 5A is located within, in this example, approximately 10 meters of the Cartesian coordinates x_1, y_1, z_1 . Also, if all four location markers 1A-4A in FIGURE 6 respond to the high-power message, then the mobile device 5A is located, in this example, within approximately 100 meters of the Cartesian coordinates of each of the location markers 1A-4A. The location information obtained by using the "Approximate Location?" message can then be used by the mobile device 5A to determine, for example, where the nearest automated teller machine is located, or travel directions from its current location to a desired location. The above-described interaction of the location markers 1A-4A with the mobile device 5A is also illustrated in FIGURE 2, where the "Approximate Location?" message can be recognized (or not) by the message processing section 22 and responded to appropriately.

[0037] FIGURE 7 illustrates exemplary operations which can be performed by the embodiment of FIGURE 6. The "Approximate Location?" message is transmitted

at a predetermined power level at 71. Thereafter, the mobile device receives the response(s) from the known location(s) at 72. Thereafter at 73, the approximate location of the mobile device 5A is estimated based on the power level that was used to transmit the "Approximate Location?" message and the location(s) that responded to the message.

[0038] It should be clear from the foregoing description that the operational features of the exemplary location markers 1, 1A and 1B can be combined together in a single location marker embodiment according to the invention, and that the operational features of the mobile devices 5, 5A and 5B can be combined together in a single mobile device embodiment according to the invention. Moreover, it will be evident to workers in the art that the above-described wireless mobile communication device embodiments according to the invention can be readily implemented by, for example, suitable modifications in software, hardware, or a combination of software and hardware in conventional wireless mobile communication devices, for example Bluetooth devices.

[0039] As demonstrated above, the present invention does not depend on the ability to receive signals directly from GPS satellites while inside large structures whose walls and ceilings attenuate or block satellite signals. Also, location estimation according to the invention does not depend on communication between wireless telephones and their base stations. If the location markers of the present invention are affixed to the ceilings and permanent walls of a large structure, a user's location can be determined anywhere within the structure, without any need for the user to exit the structure or move to its periphery for better wireless reception. Advantageously, the invention also does not depend on any clock in the mobile device that is being located, does not use measurements of range or transmission direction in the location estimation process, and does not utilize received signal power measurements as indirect measures of range. There is also no dependence on multi-element steerable antennas to determine the direction from which a transmitted signal is coming. Other exemplary advantages of the invention include the fact that the location markers of the invention can be used to transmit (e.g., relay) any desired information to the mobile devices operating in the wireless communication system, and the location markers do not require accurate and expensive clocks.

[0040] Although exemplary embodiments of the invention are described above in detail, this does not limit the scope of the invention, which can be practiced in a variety of embodiments.

Claims

1. A method of determining the location of a wireless mobile communication device operating in a wireless communication system, comprising:

the wireless mobile communication device transmitting a first waveform over a wireless communication link;
receiving the first waveform at each of a plurality of known locations;
receiving at each of the plurality of known locations a reference waveform produced by a stationary source;
for each of the known locations, producing information indicative of a phase difference between the first waveform as received at the known location and the reference waveform as received at the known location; and
using said information to determine the location of the wireless mobile communication device.

2. The method of Claim 1, wherein said transmitting step includes the wireless mobile communication device transmitting the first waveform in response to a message transmitted by a further wireless mobile communication device.
3. The method of Claim 1, wherein said first waveform and said reference waveform are periodic waveforms, said producing step including, for each of the known locations, determining a plurality of phase differences between cycles of the first waveform and corresponding cycles of the reference waveform.
4. The method of Claim 1, wherein said using step includes determining respective distances between the wireless mobile communication device and a plurality of the known locations.
5. A wireless communication system, comprising:


a wireless mobile communication device for transmitting a first waveform over a wireless communication link;
a stationary reference source for producing a reference waveform;
a plurality of stationary location markers respectively provided at a plurality of predetermined locations for receiving the first waveform, each said location marker coupled to said reference source for receiving the reference waveform;
each said location marker responsive to the first waveform and the reference waveform for producing information indicative of a phase difference between the first waveform and the reference waveform as received at said location marker; and
a location determiner coupled to said location markers for receiving said information from said location markers and determining from said information the location of said wireless mobile


communication device.

6. The system of Claim 5, wherein said reference source includes one of a GPS receiver, an oven-stabilized quartz oscillator, a Cesium atomic oscillator and a Rubidium atomic oscillator. 5
7. The system of Claim 5, including a further wireless mobile communication device coupled to said first-mentioned wireless mobile communication device via a wireless communication link for requesting said first-mentioned wireless mobile communication device to transmit said first waveform, and wherein said location determiner is provided in said further wireless mobile communication device. 10 15
8. A wireless mobile communication device, comprising:
an output for transmitting a wireless signal at a predetermined transmission power level; 20
an input for receiving a wireless response to said wireless signal, said wireless response including information indicative of a location of a source of said response; and 25
a location determiner coupled to said input and responsive to said information and said predetermined transmission power level for determining a location of said wireless mobile communication device. 30
9. The wireless mobile communication device of Claim 8, wherein said input is for receiving a plurality of wireless responses to said wireless signal, each of said wireless responses including information indicative of a location of a source of said wireless response, said location determiner responsive to said predetermined transmission power level and said information in said plurality of wireless responses for determining the location of said wireless mobile communication device. 35 40
10. The wireless mobile communication device of Claim 8, wherein said location determiner is operable for determining that said wireless mobile communication device is located within a predetermined distance of each of the plurality of sources. 45

50

55








FIG. 5





FIG. 7






FIG. 4





FIG. 6





(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
16.04.2003 Bulletin 2003/16

(51) Int Cl.7: **H04Q 7/38**

(43) Date of publication A2:
04.12.2002 Bulletin 2002/49

(21) Application number: **02100581.4**

(22) Date of filing: **30.05.2002**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• GILKES, Alan M.
Plano, TX 75075 (US)
• PANASIK, Carl
Garland, TX 75044 (US)

(30) Priority: **01.06.2001 US 872598**


(71) Applicant: **Texas Instruments Incorporated**
Dallas, Texas 75251 (US)

(74) Representative: **Holt, Michael et al**
Texas Instruments Ltd.,
EPD MS/13,
800 Pavilion Drive
Northampton Business Park,
Northampton NN4 7YL (GB)

(54) **Location estimation in narrow bandwidth wireless communication systems**

(57) The phase difference between a known stable reference signal (11) and a known signal output by a wireless mobile communication device (5, 5B) is determined at several known locations (1-4, 1B-4B). The location of the wireless mobile communication device is then determined from the phase difference information.

Also, the approximate location of a wireless mobile communication device (5A) can be estimated by transmitting a message from the device at a predetermined power level (71), and determining where among a plurality of predetermined locations (1A-4A) the transmitted message has been received.





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 02 10 0581

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	WO 97 22888 A (SIGNATRON TECHNOLOGY CORP.) 26 June 1997 (1997-06-26) * abstract; figure 1 * * page 9, line 15 - line 28 * * page 15, line 17 - line 34 *	1,5	H04Q7/38
A	*Idem*	2-4,6,7	
X	US 5 493 308 A (BINGHAM ET AL.) 20 February 1996 (1996-02-20) * abstract; figures 1,2 * * column 3, line 6 - column 4, line 53 *	1,5	
A	*Idem*	2-4,6,7	
X	US 5 317 323 A (KENNEDY ET AL.) 31 May 1994 (1994-05-31) * abstract; figure 1 * * column 3, line 15 - column 4, line 9 *	1,5	
A	*Idem*	2,4,6,7	
X	US 5 890 068 A (FATTOUCHE ET AL.) 30 March 1999 (1999-03-30) * abstract; claim 1; figures 2,4 *	1,5	H04Q G01S
X	WO 95 26510 A (QUALCOMM INC.) 5 October 1995 (1995-10-05) * abstract; figure 4 * * page 7, line 34 - page 8, line 2 * * page 11, line 13 - page 12, line 15 *	1,5	
X	US 5 589 838 A (MCEWAN) 31 December 1996 (1996-12-31) * abstract; figure 1 * * column 3, line 14 - column 4, line 3 * * column 5, line 3 - line 65 *	1,5	
-/--			
The present search report has been drawn up for all claims			
Place of search		Date of completion of the search	Examiner
BERLIN		14 February 2003	Danielidis, S
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application I : document cited for other reasons & : member of the same patent family corresponding document	



European Patent
Office

Application Number

EP 02 10 0581

CLAIMS INCURRING FEES

The present European patent application comprised at the time of filing more than ten claims.

- ☐ Only part of the claims have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims and for those claims for which claims fees have been paid, namely claim(s):
- ☐ No claims fees have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims.

LACK OF UNITY OF INVENTION

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

see sheet B

- ☒ All further search fees have been paid within the fixed time limit. The present European search report has been drawn up for all claims.
- ☐ As all searchable claims could be searched without effort justifying an additional fee, the Search Division did not invite payment of any additional fee.
- ☐ Only part of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the inventions in respect of which search fees have been paid, namely claims:
- ☐ None of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims, namely claims:



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 10 0581

DOCUMENTS CONSIDERED TO BE RELEVANT				
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)	
X	WO 01 23904 A (NOKIA CORP.) 5 April 2001 (2001-04-05) * abstract; figure 1 * * page 12, line 14 - line 34 * * page 16, line 11 - page 17, line 27 *	1,5		
X	WO 00 38460 A (KONINKLIJKE PHILIPS ELECTRONICS N.V.) 29 June 2000 (2000-06-29) * abstract; figures 1-3 * * page 7, line 29 - page 8, line 13 * * page 9, line 3 - line 23 * * page 10, line 2 - line 6 *	8-10		
P,X	WO 01 58098 A (QUALCOMM INC.) 9 August 2001 (2001-08-09) * abstract; figures 3,5 * * page 8, line 3 - line 29 * * page 9, line 19 - line 27 *	8-10		
Y	DE 35 16 357 A (ROBERT BOSCH GMBH) 13 November 1986 (1986-11-13) * abstract; figures 1,2 * * column 3, line 14 - line 47 *	8-10		TECHNICAL FIELDS SEARCHED (Int.Cl.7)
Y	US 4 533 871 A (BOETZKES) 6 August 1985 (1985-08-06) * abstract; claims 1,2; figures 1-4 *	8-10		
A	US 4 864 313 A (KONNEKER) 5 September 1989 (1989-09-05) * abstract; figures 1-3 * * column 3, line 43 - column 4, line 29 * * column 6, line 43 - line 59 *	8-10		
The present search report has been drawn up for all claims				
Place of search		Date of completion of the search	Examiner	
BERLIN		14 February 2003	Danielidis, S	
CATEGORY OF CITED DOCUMENTS * particularly relevant if taken alone * particularly relevant if combined with another document of the same category A: technical background U: non-written disclosure I: intermediate document F: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application C: document cited for other reasons S: member of the same patent family, corresponding document				

EPC FORM 1503 33.87 (P01C01)



European Patent
Office

LACK OF UNITY OF INVENTION
SHEET B

Application Number

EP 02 10 0581

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

1. Claims: 1-7

Location determination using phase differences. Mobile transmits to a plurality of fixed known receivers (markers) phase difference measured at each marker between the received signal from the mobile and a common reference. Individual results combined to calculate the position of the mobile terminal.

2. Claims: 8-10

Location determination based on power level of transmitted signal and on responses indicating location of the sources of the responses.

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 10 0581

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

14-02-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9722888	A	26-06-1997	US 5883598 A	16-03-1999
			AT 192853 T	15-05-2000
			AU 1412097 A	14-07-1997
			CA 2240628 A1	26-06-1997
			DE 69608311 D1	15-06-2000
			DE 69608311 T2	14-09-2000
			EP 0870203 A1	14-10-1998
			WO 9722888 A1	26-06-1997
			US 6259404 B1	10-07-2001
US 5493308	A	20-02-1996	NONE	
US 5317323	A	31-05-1994	NONE	
US 5890068	A	30-03-1999	CA 2213979 A1	03-04-1998
WO 9526510	A	05-10-1995	AT 208507 T	15-11-2001
			AU 2188195 A	17-10-1995
			BR 9507174 A	02-09-1997
			CA 2186378 A1	05-10-1995
			CN 1149339 A	07-05-1997
			DE 69523746 D1	13-12-2001
			DE 69523746 T2	01-08-2002
			DK 752113 T3	25-02-2002
			EP 1146350 A1	17-10-2001
			EP 0752113 A1	08-01-1997
			ES 2167425 T3	16-05-2002
			FI 963833 A	25-09-1996
			HK 1014752 A1	20-09-2002
			JP 10500771 T	20-01-1998
			WO 9526510 A1	05-10-1995
			US 6239748 B1	29-05-2001
			US 6433740 B1	13-08-2002
US 5589838	A	31-12-1996	US 5510800 A	23-04-1996
			AU 6842196 A	05-03-1997
			DE 69623481 D1	10-10-2002
			EP 0842440 A1	20-05-1998
			WO 9706447 A1	20-02-1997
			AU 3499995 A	27-03-1996
			CA 2199120 A1	14-03-1996
			EP 0779990 A1	25-06-1997
			JP 10505671 T	02-06-1998
			WO 9607928 A1	14-03-1996
			US 5576627 A	19-11-1996
			US 5774091 A	30-06-1998

EP 02 10 0581

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 02 10 0581

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

14-02-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5589838	A		US 5767953 A	16-06-1998
			US 5519400 A	21-05-1996
			US 5661490 A	26-08-1997
			US 5757320 A	26-05-1998
WO 0123904	A	05-04-2001	FI 106655 B1	15-03-2001
			AU 7295400 A	30-04-2001
			CN 1376268 T	23-10-2002
			EP 1222478 A2	17-07-2002
			WO 0123904 A2	05-04-2001
WO 0038460	A	29-06-2000	CN 1297665 T	30-05-2001
			WO 0038460 A1	29-06-2000
			EP 1057360 A1	06-12-2000
			JP 2002533692 T	08-10-2002
WO 0158098	A	09-08-2001	AU 3491201 A	14-08-2001
			EP 1256211 A2	13-11-2002
			WO 0158098 A2	09-08-2001
DE 3516357	A	13-11-1986	DE 3516357 A1	13-11-1986
US 4533871	A	06-08-1985	AU 552682 B2	12-06-1986
			AU 8677682 A	17-02-1983
			CA 1188393 A1	04-06-1985
US 4864313	A	05-09-1989	NONE	

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82